



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

**PRODUCT SPECIFICATIONS**

**PRODUCT:** EMULSION BASE STOCK

**GRADE:** Soft **PRODUCT CODE:** 13801

**DESCRIPTION:** A vacuum distilled, steam stripped bituminous residue normally used for blending emulsion base stock and other asphalt products.

**MEETS SPECIFICATIONS:** Paramount Petroleum

| <b>TESTS</b>                 | <b>ASTM<br/>METHOD</b> | <b>AASHTO<br/>METHOD</b> | <b>SPECS.</b> | <b>TYPICAL<br/>ANALYSIS<sup>1</sup></b> |
|------------------------------|------------------------|--------------------------|---------------|---|
| Penetration, 77°F, 100g, 5s  | D5                     | T49                      | 140-190       | 160                                     |
| Abs. Viscosity, 140°F, Poise | D2171                  | T202                     | 400-600       | 480                                     |
| Flash Point, C.O.C., °F      | D92                    | T48                      | 440 min       | 575                                     |
| API Gravity, 60°F            | D70                    | T228                     |               | 7.8                                     |
| Density, 60°F, lbs/gallon    | D70                    | T228                     |               | 8.46                                    |

<sup>1</sup>Values shown as typicals may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Readily Available

**DOT SHIPPING NAME:** UN3257, Elevated temperature liquid, n.o.s., 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 10-01-2007