



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

**PRODUCT SPECIFICATIONS**

**PRODUCT:** EMULSION BASE STOCK

**GRADE:** 50/60

**PRODUCT CODE:** 13802

**DESCRIPTION:** A steam refined asphalt for use in hard base asphalt emulsions.

**MEETS SPECIFICATIONS:** Paramount Petroleum

<b>TESTS</b>	<b>ASTM METHOD</b>	<b>AASHTO METHOD</b>	<b>SPECS.</b>	<b>TYPICAL ANALYSIS<sup>1</sup></b>
Penetration, 77°F, 100g, 5s	D5	T49	50-60	55
Abs. Viscosity, 140°F, Poise	D2171	T202		1975
Flash Point, C.O.C., °F	D92	T48	500 min	580
API Gravity, 60°F	D70	T228		6.0
Density, 60°F, lbs/gallon	D70	T228		8.57

<sup>1</sup>Values shown as typicals may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Readily available

**DOT SHIPPING NAME:** UN3257, Elevated temperature liquid, n.o.s., 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 5-15-2008