



PORTLAND, OR 97210

503-273-4700

PRODUCT SPECIFICATION

PRODUCT: Emulsified Asphalt

GRADE: BB-1 **PRODUCT CODE:** 13530

DESCRIPTION A anionic slow setting emulsion

MEETS SPECIFICATION:

TESTS	<u>ASTM METHOD</u>	<u>AASHTO METHOD</u>	<u>SPECS</u>	<u>TYPICAL ANALYSIS</u>
Viscosity, Saybolt, 77°F, SFS	D244	T59	20-100	30
Storage Stability, 24H, %	D244	T59	1 Max	0.1
Ph	E70	T200		10.5
Sieve Test, % 20 Mesh	D244	T59	.1 Max	0.05
Sieve Test, % 80 Mesh	D244	T59	.5 Max	0.30
Density, 60F° lbs/gallon	D244	T59		8.5
Residue by Evaporation, %	D244	T59	57 Min	62
Tests on Residue by Evaporation				
Penetration, 77°F, 100g, 5s	D5	T49	5-10dmm	7
Softening Point F	D36		200-220	210

Values listed are typical results.

AVAILABILITY: Readily available.

DOT SHIPPING NAME: Elevated temperature, liquid, n.o.s, 9, UN 3257, III

DOT PLACARD: 3257

RELEASED: 4/11/2007